

MULTITASKS

MTM - MTM/HP

Rock grinder, stabilizer, stone crusher and asphalt shredder for PTO tractors.



240-360 hp



Depth 40 cm



Variable displacement chamber

STANDARD EQUIPMENT

Hydraulic front hood	Gearbox with freewheel
Hydraulic rear hood	PTO shaft (MTM/HP)
Interchangeable inner antiwear plates in Hardox®	Friction clutches
Enclosed machine body	PTO shaft with cam clutch (MTM)
Variable displacement chamber	Bolted-on rotor shafts (in forged steel)
Bolted grid on rear hood	Adjustable Hardox® counter-blade
Inside lateral protection	Adjustable skids
Protection chains	Dozing blades with spring system
Transmission with side gearbox	

OPTIONS

Extended 3 point linkage	Water spray system WSS High Flow
Multiple tooth options	FCS full control system
Hydraulic top link	

MODEL	MTM 200	MTM 225	MTM/HP 200	MTM/HP 225
Tractor (hp)	240-360	240-360	300-360	300-360
PTO (rpm)	1000	1000	1000	1000
Working width (mm)	2053	2293	2053	2293
Total width (mm)	2495	2735	2495	2735
Weight (Kg)	5850	6350	5900	6400
Rotor diameter (mm)	940	940	940	940
ROTOR G/3				
Working depth (mm) (Max. 1-Max. 2)	250-400	250-400	250-400	250-400
No. teeth type G/3+STC/3/FP+STC/FP	94+4+4	106+4+4	94+4+4	106+4+4
ROTOR R				
Working depth (mm) (Max. 1-Max. 2)	240-400	240-400	240-400	240-400
No. teeth type R+R/HD+STC/3/FP+STC/FP	126+20+4+4	144+20+4+4	126+20+4+4	144+20+4+4

Max.1: with rotor only **Max.2:** maximum depth (maximum working depth depending on ground conditions)

This information refers to the machine equipped as standard. The technical data in this catalogue may be altered without prior notice.

ROTOR TYPE G



G/3
(standard)

G/3/HD
(option)

Adaptor G/3 R 44
(option)

ROTOR TYPE R



R 65
(standard)

R/HD 65
(option)

R 44
(option)

Adaptor R 65
(option)

STC/3/FP
(side scraper)

R/HD 65
(side scraper)